



SEICO HIDRÁULICA Y LUBRICACIÓN S.A. DE C.V.

Acero al carbón / carbon steel


SECCIÓN 12

BANJOS

**RACOR ORIENTABLE
BSP S/METAL C1H11**

high Pressure Banjo Elbow
L and S Series
Thread: BSPP
sealing by external metallic
sealing ring (DKRA) and
O-ring Viton

SERIES:
LL= Doble Ligera
L= Ligera
S= Pesada



CODIGO	MATERIAL	TIPO	D1 (MM)	T1 (MM)	D2(MM)	L1(MM)	L2(MM)	S1(MM)	BAR	PSI
217521	ACERO AL CARBON	L	6	1/8	14	27	13	17	500	7251.9
202410	ACERO AL CARBON	L	8	1/4	18	29	15	22	500	7251.9
209885	ACERO AL CARBON	L	10	1/4	18	30	16	22	500	7251.9
238065	ACERO AL CARBON	L	12	3/8	22	33	18	27	400	5801.5
217525	ACERO AL CARBON	L	15	1/2	26	37	21	32	400	5801.5
217526	ACERO AL CARBON	L	18	1/2	26	37	21	32	400	5801.5
217527	ACERO AL CARBON	L	22	3/4	32	43	28	41	250	3625.9
211422	ACERO AL CARBON	L	28	1	39	48	32	50	250	3625.9
217529	ACERO AL CARBON	L	35	1,1/4	49	57	36	60	250	3625.9
211424	ACERO AL CARBON	L	42	1,1/2	55	63	41	70	250	3625.9
217531	ACERO AL CARBON	S	6	1/4	18	31	17	22	800	11603.0
211552	ACERO AL CARBON	S	8	1/4	18	31	17	22	800	11603.0
202421	ACERO AL CARBON	S	10	3/8	22	35	19	27	800	11603.0
217534	ACERO AL CARBON	S	12	3/8	22	35	19	27	630	9137.4
211425	ACERO AL CARBON	S	14	1/2	26	40	23	32	630	9137.4
217536	ACERO AL CARBON	S	16	1/2	26	40	22	32	630	9137.4
218314	ACERO AL CARBON	S	20	3/4	32	48	27	41	420	6091.5
217538	ACERO AL CARBON	S	25	1	39	56	32	50	420	6091.5
217539	ACERO AL CARBON	S	30	1,1/4	49	64	37	60	420	6091.5
217540	ACERO AL CARBON	S	38	1,1/2	55	72	42	70	420	6091.5

Acero al carbón / carbon steel **Página 94**

Calle Juan Gutemberg 219, Col. Tecnológico Puebla, Puebla. México. CP 72210 Tel: 01(222) 274.42.91, 168.49.49 S/C 01 800.836.66.11

www.seicohidraulica.com