

SECCION 2

RACORES

RACOR RECTO BSP S/METALICO
C2B11

Male Stud Connector

L Series

Thread: BSPP



Metallic sealing edge Form B

SERIES:

LL= Doble Ligera

L= Ligera

S= Pesada

SEICO HIDRÁULICA Y
LUBRICACIÓN S.A. DE C.V.

CODIGO	MATERIAL	TIPO	D1 (MM)	T	L1(MM)	L2(MM)	S1(MM)	BAR	PSI
102187	ACERO INOXIDABLE	LL	4	1/8	27	9,5	14	100	1450.4
102205	ACERO INOXIDABLE	LL	6	1/8	28	8	14	100	1450.4
102206	ACERO INOXIDABLE	LL	6	1/4	33	9,5	19	100	1450.4
102273	ACERO INOXIDABLE	LL	8	1/8	28	9	14	100	1450.4
102274	ACERO INOXIDABLE	LL	8	1/4	33	9	19	100	1450.4
102220	ACERO INOXIDABLE	L	6	1/8	31	8,5	22	315	4568.7
102221	ACERO INOXIDABLE	L	6	1/2	41	12	27	315	4568.7
102225	ACERO INOXIDABLE	L	6	1/4	37	10	19	315	4568.7
102231	ACERO INOXIDABLE	L	6	3/8	38	11,5	22	315	4568.7
102289	ACERO INOXIDABLE	L	8	1/4	37	10	19	315	4568.7
102290	ACERO INOXIDABLE	L	8	1/2	41	12	27	315	4568.7
102293	ACERO INOXIDABLE	L	8	1/8	33	9,5	14	315	4568.7
102296	ACERO INOXIDABLE	L	8	3/4	44	13	32	315	4568.7
102299	ACERO INOXIDABLE	L	8	3/8	37	10	22	315	4568.7
102353	ACERO INOXIDABLE	L	10	1/4	38	11	19	315	4568.7
102354	ACERO INOXIDABLE	L	10	1/2	42	13	27	315	4568.7
102357	ACERO INOXIDABLE	L	10	1/8	33	10,5	17	315	4568.7
102360	ACERO INOXIDABLE	L	10	3/4	45	14,5	32	315	4568.7
102363	ACERO INOXIDABLE	L	10	3/8	39	12,5	22	315	4568.7
102421	ACERO INOXIDABLE	L	12	3/8	39	12,5	22	315	4568.7
102422	ACERO INOXIDABLE	L	12	1/2	42	13	27	315	4568.7
102425	ACERO INOXIDABLE	L	12	1/4	39	12	19	315	4568.7
102428	ACERO INOXIDABLE	L	12	1/8	35	12,5	19	315	4568.7
102431	ACERO INOXIDABLE	L	12	3/4	45	14	32	315	4568.7
102516	ACERO INOXIDABLE	L	15	1/2	40	14	27	250	3625.9

SECCION 2

RACORES

RACOR RECTO BSP S/METALICO C2B11

Male Stud Connector

L Series

Thread: BSPP

Metallic sealing edge Form B



SERIES:

LL= Doble Ligera

L= Ligera

S= Pesada

SEICO HIDRÁULICA Y LUBRICACIÓN S.A. DE C.V.



CODIGO	MATERIAL	TIPO	D1 (MM)	T	L1(MM)	L2(MM)	S1(MM)	BAR	PSI
102517	ACERO INOXIDABLE	L	15	1	49	16	41	250	3625.9
102518	ACERO INOXIDABLE	L	15	1/4	41	14	24	250	3625.9
102521	ACERO INOXIDABLE	L	15	1/8	37	14	24	250	3625.9
102526	ACERO INOXIDABLE	L	15	3/4	46	15	32	250	3625.9
102529	ACERO INOXIDABLE	L	15	3/8	40	13,5	24	250	3625.9
102586	ACERO INOXIDABLE	L	18	1/2	45	14,5	27	250	3625.9
102587	ACERO INOXIDABLE	L	18	1	49	14,5	41	250	3625.9
102588	ACERO INOXIDABLE	L	18	1/4	43	14,5	27	250	3625.9
102591	ACERO INOXIDABLE	L	18	1/8	39	14,5	27	250	3625.9
102596	ACERO INOXIDABLE	L	18	3/4	47	14,5	32	250	3625.9
102599	ACERO INOXIDABLE	L	18	3/8	43	14,5	27	250	3625.9
102647	ACERO INOXIDABLE	L	22	3/4	49	16,5	32	160	2320.6
102648	ACERO INOXIDABLE	L	22	1	52	17,5	41	160	2320.6
102649	ACERO INOXIDABLE	L	22	1/2	47	16,5	32	160	2320.6
102655	ACERO INOXIDABLE	L	22	3/8	45	16,5	32	160	2320.6
102657	ACERO INOXIDABLE	L	22	1, 1/4	54	17,5	50	160	2320.6
102694	ACERO INOXIDABLE	L	28	1	52	17,5	41	160	2320.6
102695	ACERO INOXIDABLE	L	28	1/2	48	17,5	41	160	2320.6
102698	ACERO INOXIDABLE	L	28	1, 1/2	59	20,5	55	160	2320.6
102700	ACERO INOXIDABLE	L	28	3/4	50	17,5	41	160	2320.6
102702	ACERO INOXIDABLE	L	28	1, 1/4	54	17,5	50	160	2320.6
102737	ACERO INOXIDABLE	L	35	1, 1/4	59	17,5	50	160	2320.6
102738	ACERO INOXIDABLE	L	35	1	57	17,5	46	160	2320.6
102739	ACERO INOXIDABLE	L	35	1/2	53	17,5	46	160	2320.6
102744	ACERO INOXIDABLE	L	35	1,1/2	63	19,5	55	160	2320.6

SECCION 2

RACORES

RACOR RECTO BSP S/METALICO
C2B11

Male Stud Connector

L Series

Thread: BSPP



Metallic sealing edge Form B

SERIES:

LL= Doble Ligera

L= Ligera

S= Pesada

SEICO HIDRÁULICA Y
LUBRICACIÓN S.A. DE C.V.

CODIGO	MATERIAL	TIPO	D1 (MM)	T	L1(MM)	L2(MM)	S1(MM)	BAR	PSI
102746	ACERO INOXIDABLE	L	35	3/4	55	17,5	46	160	2320.6
102773	ACERO INOXIDABLE	L	42	1,1/2	94	19	55	160	2320.6
102774	ACERO INOXIDABLE	L	42	1	60	19	55	160	2320.6
102777	ACERO INOXIDABLE	L	42	1,1/4	62	19	55	160	2320.6
102247	ACERO INOXIDABLE	S	6	1/4	40	13	19	630	9137.4
102248	ACERO INOXIDABLE	S	6	1/2	47	18	27	630	9137.4
102251	ACERO INOXIDABLE	S	6	1/8	35	12,5	17	630	9137.4
102253	ACERO INOXIDABLE	S	6	3/4	51	20	32	630	9137.4
102255	ACERO INOXIDABLE	S	6	3/8	42	15,5	22	630	9137.4
102319	ACERO INOXIDABLE	S	8	1/4	42	15	19	630	9137.4
102320	ACERO INOXIDABLE	S	8	1/2	47	18	27	630	9137.4
102326	ACERO INOXIDABLE	S	8	3/8	42	15,5	22	630	9137.4
102386	ACERO INOXIDABLE	S	10	3/8	43	15	22	630	9137.4
102387	ACERO INOXIDABLE	S	10	1/2	48	17,5	27	630	9137.4
102389	ACERO INOXIDABLE	S	10	1/4	43	14,5	19	630	9137.4
102391	ACERO INOXIDABLE	S	10	1/8	39	14	19	630	9137.4
102393	ACERO INOXIDABLE	S	10	3/4	50	17,5	32	630	9137.4
102460	ACERO INOXIDABLE	S	12	3/8	46	17	22	630	9137.4
102461	ACERO INOXIDABLE	S	12	1/2	48	17,5	27	630	9137.4
102464	ACERO INOXIDABLE	S	12	1/4	45	16,5	22	630	9137.4
102468	ACERO INOXIDABLE	S	12	3/4	50	17,5	32	630	9137.4
102481	ACERO INOXIDABLE	S	14	1/2	51	19	27	630	9137.4
102482	ACERO INOXIDABLE	S	14	1	60	23	41	630	9137.4
102483	ACERO INOXIDABLE	S	14	1/4	46	16	22	630	9137.4
102488	ACERO INOXIDABLE	S	14	3/4	55	21	32	630	9137.4

SECCION 2

RACORES

RACOR RECTO BSP S/METALICO
C2B11

Male Stud Connector

L Series

Thread: BSPP



Metallic sealing edge Form B

SERIES:

LL= Doble Ligera

L= Ligera

S= Pesada

SEICO HIDRÁULICA Y
LUBRICACIÓN S.A. DE C.V.

CODIGO	MATERIAL	TIPO	D1 (MM)	T	L1(MM)	L2(MM)	S1(MM)	BAR	PSI
102490	ACERO INOXIDABLE	S	14	3/8	48	18,5	22	630	9137.4
102555	ACERO INOXIDABLE	S	16	1/2	51	18,5	27	630	9137.4
102557	ACERO INOXIDABLE	S	16	1/4	48	18	24	630	9137.4
102562	ACERO INOXIDABLE	S	16	3/4	55	20,5	32	630	9137.4
102564	ACERO INOXIDABLE	S	16	3/8	48	18	27	630	9137.4
102619	ACERO INOXIDABLE	S	20	3/4	58	20,5	32	400	5801.5
102620	ACERO INOXIDABLE	S	20	1	62	22,5	41	400	5801.5
102621	ACERO INOXIDABLE	S	20	1/2	56	20,5	32	400	5801.5
102624	ACERO INOXIDABLE	S	20	1,1/2	69	25,5	55	400	5801.5
102626	ACERO INOXIDABLE	S	20	3/8	54	20,5	32	400	5801.5
102628	ACERO INOXIDABLE	S	20	1,1/4	64	22,5	50	400	5801.5
102672	ACERO INOXIDABLE	S	25	1	65	23	41	400	5801.5
102673	ACERO INOXIDABLE	S	25	1/2	61	23	41	400	5801.5
102675	ACERO INOXIDABLE	S	25	1,1/2	72	26	55	400	5801.5
102677	ACERO INOXIDABLE	S	25	3/4	63	23	41	400	5801.5
102679	ACERO INOXIDABLE	S	25	1,1/4	67	23	50	400	5801.5
102716	ACERO INOXIDABLE	S	30	1,1/4	70	23,5	50	400	5801.5
102717	ACERO INOXIDABLE	S	30	1	68	23,5	46	250	3625.9
102718	ACERO INOXIDABLE	S	30	1/2	64	23,5	46	250	3625.9
102722	ACERO INOXIDABLE	S	30	1,1/2	75	26,5	55	250	3625.9
102758	ACERO INOXIDABLE	S	38	1,1/2	79	26	55	250	3625.9
102759	ACERO INOXIDABLE	S	38	1	75	26	55	250	3625.9
102761	ACERO INOXIDABLE	S	38	3/4	73	26	55	250	3625.9
102762	ACERO INOXIDABLE	S	38	1,1/4	77	26	55	250	3625.9
123823	ACERO INOXIDABLE	S	20	1/4	54	20,5	32	250	3625.9