




Tuerca de Apriete

SAE JS14 JIC Flared 37



No. Item	M - Tubo Diámetro	W - Tubo Diámetro	JIC 37° Thread	L1	Material
200201	6 mm	1/4 in	7/16-20	15.5 mm	Acero al carbón
200202	8 mm	5/16 in	1/2--20	17.0 mm	Acero al carbón
200203	10 mm	3/8 in	9/16-18	18.3 mm	Acero al carbón
200204	12 mm	1/2 in	3/4--16	21.3 mm	Acero al carbón
200205	14 mm				
	15 mm				
	16 mm	5/8 in	7/8--14	24.6 mm	Acero al carbón
200206	18 mm				
	20 mm	3/4 in	1 1/16-12	25.9 mm	Acero al carbón
200207	25 mm	1 in	1 5/16-12	28.4 mm	Acero al carbón
200208	30 mm				
	32 mm	1 1/4 in	1 5/8-12	31.0 mm	Acero al carbón
200209	38 mm	1 1/2 in	1 7/8-12	35.8 mm	Acero al carbón
210201	6 mm	1/4 in	7/16-20	15.5 mm	Acero inoxidable
210202	8 mm	5/16 in	1/2--20	17.0 mm	Acero inoxidable
210203	10 mm	3/8 in	9/16-18	18.3 mm	Acero inoxidable
210204	12 mm	1/2 in	3/4--16	21.3 mm	Acero inoxidable
210205	14 mm				
	15 mm				
	16 mm	5/8 in	7/8--14	24.6 mm	Acero inoxidable
210206	18 mm				
	20 mm	3/4 in	1 1/16-12	25.9 mm	Acero inoxidable
210207	25 mm	1 in	1 5/16-12	28.4 mm	Acero inoxidable
210208	30 mm				
	32 mm	1 1/4 in	1 5/8-12	31.0 mm	Acero inoxidable
210209	38 mm	1 1/2 in	1 7/8-12	35.8 mm	Acero inoxidable